

LED Flood Light



Features

- Power Factor: ≥ 0.90
- LED Chip: Samsung
- CRI: $R_a \geq 70$
- Efficiency: 110lm/w
- Material: Aluminum alloy + PC optics lens + glass
- Standard color: Silver or black
- Working Temperature: $-40^{\circ}\text{F} \sim 122^{\circ}\text{F}$
- L70(hours): > 54000 hours
- Total Harmonic Distortion: $< 15\%$

Application

General flood requirements, bulletin/billboard, sports field and flag poles utilizing advanced refractive LED optical system providing high uniformity, excellent light distribution

Ordering Information

Model	Wattage	CCT	Lumens	Frequency	Voltage	Warranty	DIM
FL-W030	30watt	5000K	3300lm	50/60HZ	100-277V	5 years	NO
FL-W050	50watt	5000K	5500lm	50/60HZ	100-277V	5 years	NO
FL-W100	100watt	5000K	11000lm	50/60HZ	100-277V	5 years	NO
FL-W140	140watt	5000K	15400lm	50/60HZ	100-277V	5 years	NO
FL-W210	210watt	5000K	23100lm	50/60HZ	100-277V	5 years	NO
FL-W280	280watt	5000K	30800lm	50/60HZ	100-277V	5 years	NO

